Delock LTE Antenna Dual Band WLAN ac/a/b/g/n RP-SMA plug 1 - 4 dBi omnidirectional rotatable with tilt joint white

Description

This LTE antenna by Delock allows the usage of different LTE bands inside and outside. It is completely compatible to GSM, LTE, UMTS, Bluetooth, WLAN 2.4 / 5.1 GHz, ZigBee, DECT and Z-Wave.



Item no. 12431

EAN: 4043619124312

Country of origin: Taiwan, Republic of China

Package: Zip poly bag

Specification

- Connector: 1 x RP-SMA plug
- Frequency range:
  698 - 791 MHz
  824 - 960 MHz
  1710 - 2170 MHz
  2400 - 2500 MHz
  2570 - 2700 MHz
  5150 - 5875 MHz
- Bluetooth, GSM, LTE, UMTS, WLAN 2,4 / 5,0 GHz, ZigBee 2,4 GHz, Z-Wave, DECT, LoRa 868 / 915 MHz
- Antenna gain: 1 - 4 dBi
- Impedance: 50 Ohm
- VSWR:
  698 - 791 MHz: 5.0
  824 - 960 MHz: 5.0
  1710 - 2170 MHz: 2.5

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

2400 - 2500 MHz: 2.5
2570 - 2700 MHz: 2.5
5150 - 5875 MHz: 3.0

- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS UV resistant
- Dimensions (LxWxH): ca. 156.16 x 39.78 x 6.17 mm
- Diameter RP-SMA: ca. 13.5 mm


System requirements

- Device with a free RP-SMA connector

Package content

- Antenna

Images



© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.