

# Delock LPWAN 868 MHz Antenna SMA plug 4.5 dBi fixed omnidirectional with connection cable RG-58 C/U 2.5 m outdoor black

## Description

This antenna by Delock allows the usage of the 868 MHz band indoors and outdoors.

#### LPWAN

LPWAN (Low Power Wide Area Network) are radio networks that cover large distances. They are characterized by a high reception sensitivity and by a low energy consumption.



#### Item no. 12567

EAN: 4043619125678 Country of origin: China Package: White Box

## Specification

- Connector: 1 x SMA plug
- Frequency range: 868 MHz
- LoRa, Sigfox, ZigBee, Z-Wave
- Antenna gain: 4.5 dBi
- Impedance: 50 Ohm
- VSWR: 1.5
- Polarisation: vertical
- HBW horizontal beamwidth: 360°
- Operating temperature: -50 °C ~ 70 °C
- Mounting plate: iron chromed
- Colour: black
- · Cable type: coaxial
- Cable type: RG-58 C/U
- Cable attenuation: 0.73 dB @ 1.0 GHz per meter
- Cable diameter: ca. 4.95 mm
- Smallest bending radius: 20,00 mm
- Cable length incl. connectors: ca. 2.5 m

#### **DATASHEET**



- Dimensions (LxD): ca. 300 x 33 mm
- Dimensions Mounting plate (LxWxH): ca. 170 x 40 x 20 mm
- Maximum wind speed: 60 m/s

#### System requirements

• Device with a free SMA connector

#### Package content

- Antenna
- Fixing plate

#### Images





#### General

Suitable for outdoor:	yes
Interface	

connector:	1 x SMA plug

## **Technical characteristics**

Frequency range:	868 MHz
Antenna gain:	4.5 dBi
Impedance:	50 Ω
Operating temperature:	-50 °C ~ 70 °C
Polarisation:	vertical
Power handling:	100 W

## **Physical characteristics**

Weight:	0.19 kg
Cable category:	coaxial
Cable type:	RG-58 C/U
Cable attenuation:	0.73 dB @ 1.0 GHz per meter
Cable colour:	black
Cable length incl. connector:	2.5 m
Smallest bending radius:	20 mm
Dimensions (LxØ):	300.0 x 33.0 mm
Maximum wind speed:	60 m/s