Delock External Enclosure mSATA SSD > Multiport SuperSpeed USB 10 Gbps (USB 3.1 Gen 2)

Description

In the aluminum enclosure by Delock an mSATA SSD can be installed. The enclosure can be connected via USB Type-C™ to the PC or laptop. By using optional cable, it is possible to connect this enclosure to a USB Type-A, eSATA or eSATAp interface.



Item no. 42566

EAN: 4043619425662

Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

- Connector:
  external:
  1 x Multiport SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) + eSATAp 6 Gb/s
  1 x DC for power when connecting via eSATA
  internal:
  1 x mSATA slot (half size / full size)
- For mSATA memory 1.5 Gb/s, 3 Gb/s and 6 Gb/s SSD with half size or full size
- Chipset: Asmedia ASM1351
- Data transfer rate:
  SuperSpeed USB 10 Gbps,
  SuperSpeed USB 5 Gbps,
  Hi-Speed 480 Mbps,
  Full-Speed 12 Mbps,
  Low-Speed 1.5 Mbps,
  eSATA 6 Gbps
- Enclosure with full-PCB
- LED indicator for power
- Colour: black

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- Dimensions (LxWxH): ca. 82,5 x 60 x 12 mm
- Hot Swap, Plug & Play

Power supply specification

• 5 V, ground outside, plus inside
• Dimensions:
inside: ø ca. 1.35 mm
outside: ø ca. 3.5 mm
length: ca. 8.5 mm
• Optional power supply: Navilock 41337

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6, Mac OS 10.12
- PC or laptop with a free USB Type-C™ port

Package content

- External enclosure mSATA
- Cable USB Typ-A male to USB-C™ male, length ca. 50 cm
- Screwdriver, screws
- User manual

Images






© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Function:	Hot Swap Plug & Play
Internal construction:	full PCB
Supported operating system:	Linux Kernel 3.16 or above Mac OS 10.11 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Supported module:	mSATA full size / half size

Interface

External:	1 x Multiport USB 10 Gbps + eSATAp 6 Gb/s 1 x 5 V DC jack 3.5 mm x 1.35 mm
Internal:	1 x mSATA slot (half size / full size)

Technical characteristics

Chipset:	Asmedia ASM1351
Data transfer rate:	10 Gbps

Physical characteristics

Housing material:	Aluminium
Length:	82.5 mm
Width:	60 mm
Height:	12 mm
Colour:	black

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.