

Delock External Enclosure M.2 Key B 42/60/80 mm SSD > USB Type-C™ 3.1 Gen 2 female with write protection

Description

This enclosure by Delock enables the installation of an M.2 SSD in 2280, 2260 and 2242 format, it can be connected via USB Type-A to the PC or laptop. By the help of the switch, the inserted memory can be equipped with a write protection.



Item no. 42599

EAN: 4043619425990 Country of origin: China Package: Retail Box

Specification

· Connectors:

external: 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) USB Type- C^{TM} female

internal: 1 x 67 pin M.2 key B slot

• Chipset: JMicron JMS580

• Interface: SATA

- Supports M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA
- Maximum height of the components on the module: 1.5 mm, application of double-sided assembled modules supported
- Data transfer rate up to 6 Gbps
- 1 x switch to set write protection
- · LED indicator for power and access
- Dimensions (LxWxH): ca. 104 x 32 x 10 mm
- · Hot Plug, Plug & Play

System requirements





- Windows 7/7-64/8.1/8.1-64/10/10-64, ex Mac OS 10.9
- PC or laptop with a free USB Type-A port

Package content

- External enclosure
- Cable USB-C™ male to USB Type-A male, length ca. 40 cm
- · Mounting material
- User manual

Images









General

Function:	Hot Plug Plug & Play
Supported operating system:	Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit
Supported module:	M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA
Maximum height of the components on the module:	1.5 mm application of double-sided assembled modules supported

Interface

External:	1 x USB 10 Gbps USB Type-C™ female
Internal:	1 x 67 pin M.2 key B slot

Technical characteristics

Chipset:	JMicron JMS580
Data transfer rate:	6 Gb/s

Physical characteristics

Length:	104 mm
Width:	32 mm
Height:	10 mm