Delock External Enclosure for 2 x 2.5″ SATA HDD / SSD with RAID + 3 Port USB 3.0 Hub

Description

The aluminium enclosure by Delock enables the installation of up to two 2.5″ SATA HDDs / SSDs. When using more than one SSD, there is the possibility to use different RAID level. Additional the enclosure has a USB 3.0 hub with 3 ports on its front. The enclosure can be connected via USB Type-A to the PC or laptop.

Note

If you plug in or unplug a device during operation, it may cause all other connected devices need to reconnect.

Item no. 42606

EAN: 4043619426065

Country of origin: China

Package: Retail Box

Specification

- Connectors:
  external:
  back side:
  1 x USB 3.0 Type-B female
  1 x DC 12 V power connector
  front side:
  2 x USB 3.0 Type-A female
  1 x USB 3.0 Type-A female - Battery Charging specification BC1.2
  internal:
  2 x SATA 6 Gb/s 22 pin receptacle
- Chipset: VIA VL813, JMicron JMS561
- HDD height up to 12.5 mm
- Data transfer rate up to:
  SuperSpeed USB 5 Gbps,
  Hi-Speed 480 Mbps,
  Full-Speed 12 Mbps,
  Low-Speed 1.5 Mbps
- Supports RAID 0, RAID 1, JBOD, Port Multiplier
- LED indicator for power, access and RAID mode

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- Supports automatically rebuild
- 1 x On / Off switch
- 1 x on / off switch for the fan
- 1 x Reset button
- 1 x DIP switch for RAID mode
- Metal housing
- Colour: black
- Dimensions (LxWxH): ca. 135 x 99 x 59 mm
- Hot Plug, Plug & Play

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A
- Output: 12 V / 2 A
- Ground outside, plus inside
- Dimensions:
  inside: ø ca. 2.1 mm
  outside: ø ca. 5.5 mm
  length: ca. 9.5 mm

System requirements

- Chrome OS
- Linux Kernel 3.3 or above
- Mac OS 10.13.6 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- External enclosure
- 1 x cable USB 3.0 A male to USB 3.0 B male, length ca. 1 m
- Power supply
- Screws
- User manual

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

Images

DELOCK
we move the world
RAID
5 Gbps
For two 2.5" SATA hard drives or SSDs
3 Port USB 3.0 Hub with one Battery Charging port
External Enclosure for 2 x 2.5" SATA HDD / SSD
+ USB 3.0 Hub

General

Function:	Battery Charging BC1.2 Hot Plug Plug & Play
Suitable for data medium:	2.5″
Supported operating system:	Chrome OS Linux Kernel 3.3 or above Mac OS 10.13.6 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	1 x DC 12 V power connector 1 x USB 5 Gbps Type-A female - Battery Charging specification BC1.2 2 x USB 5 Gbps Type-A female 1 x USB 5 Gbps Type-B female
Internal:	2 x SATA 22 Pin Buchse

Technical characteristics

Chipset:	VIA VL813 JMicron JMS561
RAID function:	JBOD 0 1 Port Multiplier

Physical characteristics

Housing material:	metal
Length:	135 mm
Width:	99 mm

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

Height:	59 mm
Colour:	black

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.