

Delock External Enclosure for 3.5" SATA HDD with USB Type-C™ female transparent - tool free

Description

This plastic enclosure by Delock can be used for the installation of a 3.5" SATA hard drive. The included USB cables allow the connection to a free USB Type-A or USB-CTM port.

Transparent enclosure with stand

The **sturdy**, **transparent plastic housing** provides a view inside to quickly see which memory is inside. A stand is supplied for vertical operation.

HDD installation without tools

The special feature of this enclosure is that **no tools** are required to install the HDD. The lid can be pushed backwards by a little pressure, the HDD will be attached to the SATA port and then the lid is reattached until it locks.



Item no. 42623

EAN: 4043619426232 Country of origin: China Package: Retail Box

Specification

• Connectors:

external:

1 x SuperSpeed USB (USB 3.2 Gen 1) USB Type- C^{TM} female

1 x DC jack

internal:

1 x SATA 6 Gb/s 22 pin receptacle

- · On / Off switch
- Suitable for 3.5" SATA HDD:

SATA HDD up to 6 Gb/s

HDD up to 10 TB

- Chipset: VIA VL716
- Data transfer rate:

SuperSpeed USB 5 Gbps,

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

LED indicator for power and access

DATASHEET



- Transparent plastic housing
- Dimensions (LxWxH): ca. 179 x 116 x 30 mm
- Hot Swap, Plug & Play

Power supply specification

• Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 1 A

• Output: 12 V / 2 A

• Ground outside, plus inside

• Dimensions:

inside: ø ca. 2.0 mm outside: ø ca. 5.5 mm length: ca. 10 mm

System requirements

- Chrome OS 75.0 or above
- Linux Kernel 3.3 or above
- Mac OS 10.14.6 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-C[™] port or
- PC or laptop with a free USB Type-A port

Package content

- 3.5" external enclosure
- Cable USB-C™ male to USB-C™ male, length ca. 50 cm
- Cable USB-C™ male to USB Type-A male, length ca. 1 m
- Stand
- Power supply
- User manual



Images













General

Function:	Hot Swap Plug & Play
Suitable for data medium:	2.5" 3.5" SSD or HDD
Supported operating system:	Chrome OS 75.0 or above Linux Kernel 3.3 or above Mac OS 10.14.6 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	1 x DC jack 1 x USB 5 Gbps USB Type-C [™] female
Internal:	1 x SATA 6 Gb/s 22 pin receptacle

Technical characteristics

Chipset: VIA VL716

Physical characteristics

Housing material:	Plastic
Length:	179 mm
Width:	116 mm
Height:	30 mm
Colour:	transparent