

Item No. 47198

Delock 3.5" Mobile Rack for 1 x 2.5" SATA HDD

Description

This Delock Mobile Rack is designed for external or internal connection of a 2.5" SATA HDD. Insert the HDD directly into the frame and connect it either externally to a free USB port or with the help of an optional cable to a Power Over eSATA port, or internally to SATA. The dimension of the frame complies to a standard 3.5" HDD. Thus you can install the frame into a 3.5" slot as well as into a 5.25" mobile rack.



Specification

- 3.5" HDD dimension
- Connector:
 - inside:
 - 1 x SATA 22 pin male ([NSS connector](#))
 - outside:
 - 1 x SATA 22 pin female
 - 1 x USB 2.0 Type Mini-B female
- Suitable for 2.5" SATA HDD / SSD:
 - HDD height 9.5 mm
 - SATA HDD / SSD up to 6 Gb/s
 - supports 5 V HDD / SSD
- Possible applications:
 1. internally in a 3.5" bay
 2. inside a 5.25" mobile rack
 3. externally over USB
 4. externally over eSATAp (cable optional)
- Hot Swap
- With special SATA NSS connector inside to protect the SATA connector of the HDD from wear at each change
- OS independent, no driver installation necessary

System requirements

- For external using:
 1. PC or notebook with a free USB port
 2. PC or notebook with a free Power Over eSATA port (optional eSATAp cable item 84397 / 84396 / 84432)
- For internal using:
 1. PC with a free 3.5" bay
 2. PC with a free SATA port
 3. SATA connecting cable

Package content

- Mobile Rack
- USB 2.0 cable
- User manual

Additional Information

EAN: 4043619471980

Country of origin: China

Package: Retail Box



Images

