

# Delock 3.5" Mobile Rack for 1 x 2.5" SATA HDD

## Description

This Delock Mobile Rack is designed for external or internal connection of a 2.5" SATA HDD. Insert the HDD directly into the frame and connect it either externally to a free USB port or with the help of an optional cable to a Power Over eSATA port, or internally to SATA. The dimension of the frame complies to a standard 3.5" HDD. Thus you can install the frame into a 3.5" slot as well as into a 5.25" mobile rack.



## Specification

- 3.5" HDD dimension
- Connectors:
  - inside:
    - 1 x SATA 22 pin male (NSS connector)
  - outside:
    - 1 x SATA 22 pin receptacle
    - 1 x USB 2.0 Type Mini-B female
- Suitable for 2.5" SATA HDD / SSD:
  - HDD height 9.5 mm
  - SATA HDD / SSD up to 6 Gb/s
  - supports 5 V HDD / SSD
- Possible applications:
  1. internally in a 3.5" bay
  2. inside a 5.25" mobile rack
  3. externally over USB
  4. externally over eSATAp (cable optional)
- Hot Swap
- With special SATA NSS connector inside to protect the SATA connector of the HDD from wear at each change
- OS independent, no driver installation necessary

## System requirements

- For external using:
  1. PC or laptop with a free USB Type-A port
  2. PC or laptop with a free Power Over eSATA port (optional eSATAp cable item 84397 / 84396 / 84432)
- For internal using:
  1. PC with a free 3.5" bay
  2. PC with a free SATA port
  3. SATA connecting cable

## Package content

- Mobile Rack
- USB 2.0 cable
- User manual

## Item no. 47198

EAN: 4043619471980

Country of origin: China

Package: Retail Box



Images

