Delock 3.5″ Mobile Rack for 1 x 2.5″ SATA / SAS HDD / SSD with vibration protection

Description

This solid metal mobile rack by Delock can be installed into a free 3.5″ bay of a PC and ensures a 360° vibration protection against horizontal and vertical vibrations through the built-in rubber bumpers. A 2.5″ SATA or SAS hard drive can be screwed into the frame. For operation with a SAS drive, a SAS controller is required. The mobile rack is equipped with a key lock to prevent unauthorised access. The hot swap function allows the exchange of the hard disk drive during operation. Furthermore the SATA plug on the outside of the device has a locking port, which will ensure the SATA cables click into place, and are protected against vibrations. The mobile rack can be used wherever the PC is subject to vibrations. As an additional inner tray for the fast hard disk change the item 47229 by Delock is available.



Item no. 47228

EAN: 4043619472284

Country of origin: China

Package: Retail Box

Special features

- „360° vibration protection“ against horizontal and vertical vibrations

Specification

- For installation into an available 3.5″ bay
- Connectors:
  inside:
  1 x SATA 6 Gb/s / SAS 12 Gb/s 29 pin receptacle
  outside:
  1 x SATA 6 Gb/s 22 pin plug with locking port
- Suitable for 2.5″ SATA / SAS HDD / SSD:
  HDD height up to 15 mm
  supports 5 V HDD / SSD
- Data transfer rate:
  SATA up to 6 Gb/s
  SAS up to 12 Gb/s

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- With key lock
- Hot Swap
- OS independent, no driver installation necessary

System requirements

- PC with one free 3.5″ bay
- A free SATA / SAS port

Package content

- 3.5″ mobile rack
- 2.5″ mobile rack inner tray
- 1 x cable SATA 22 pin receptacle with metal clip > SATA 15 pin plug and SATA 7 pin receptacle, ca. 30 cm
- 1 x cable SATA 7 pin receptacle with metal clip > SATA 7 pin receptacle with metal clip, ca. 50 cm
- 2 x keys
- 4 x rack screws
- 4 x hard drive screws
- User manual

Images

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Form factor:	3.5"
Suitable for data medium:	2.5″ SSD or HDD height up to 15.0 mm
Supported operating system:	OS independent, no driver installation necessary

Interface

External:	1 x SATA 6 Gb/s 22 pin plug with locking port
Internal:	1 x SATA 6 Gb/s 22 pin receptacle

Technical characteristics

Data transfer rate:	SAS bis zu 12 Gb/s SATA up to 6 Gb/s

Physical characteristics

Colour:	black

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.