

# Delock M.2 SSD PCIe / NVMe Key M 2280 - 128 GB

#### **Description**

This flash module by Delock is a memory in the M.2 format for the PCIe / NVMe interface. With its 80 mm length, it has the form factor 2280. The module supports PCIe x4 and has the revision 3.0. The high read and write speed supports fast data transfer even for big amount of data, which is particularly important in the photo and video range.



128 GB

#### Item no. 54078

EAN: 4043619540785
Country of origin: China
Package: Antistatic cover

### **Specification**

• Connector:

1 x 67 pin M.2 Key M male

· Capacity: 128 GB

• Interface: PCle x4 Rev. 3.0

Controller: SMI SM2263XT

Maximum read speed: 1800 MB/sMaximum write speed: 700 MB/s

• Power consumption: max. 2 W

• MTBF: 1.000.000 hours

• Flash type: TLC

• Maximum write cycles: 1000

Storage temperature: -55 °C ~ 115 °C
Operating temperature: 0 °C ~ 70 °C

• Shock: 1500G

• Operating vibration: 16G

• Humidity: 5 ~ 98 %

• Supports TRIM

• Supports S.M.A.R.T.

• Supports NVM Express (NVMe) 1.3

• Dimensions (LxWxH): ca. 80.0 x 22.0 x 2.1 mm



### System requirements

• A free M.2 key M slot based on PCle

### **Package content**

• M.2 SSD

### **Images**









### Interface

1 x 67 pin M.2 Key M male connector:

#### **Technical characteristics**

Storage temperature:	-55 °C ~ 115 °C
Read:	1800 MB/s
Maximum power consumption:	2 W
Maximum write cycles:	1000
MTBF:	1.000.000 hours
Interface:	PCIe x4 Rev. 3.0
Shock:	1500 G
Write:	700 MB/s
Capacity:	128 GB
Vibration:	16 G
Flash type:	TLC

## **Physical characteristics**

Length:	80.0 mm
Width:	22.0 mm
Height:	2.1 mm