

Delock MiniPCle mSATA 6 Gb/s flash module 8 GB -40°C ~ +85°C

Description

This mSATA flash module supports the SATA 6 Gb/s specification and impresses, compared to a standard module, with its more effective boot time and lower power consumption. It is designed for industrial use, has an extended temperature range of -40 °C +85 °C and supports the iSmart function (iSMART is a powerful, easy-to-use solid-state drive (SSD) and hard disk drive (HDD) monitoring tool. It allows system integrators to track important disk information, such as temperature, storage space, bad blocks, lifespan, and firmware, all under one platform). Furthermore, the module is vibration resistant. The intelligent recovery system provides testing and data recovery during voltage fluctuations.

The module can be configured as a boot device as well as for mere data storage.



8 GB

Item no. 54705

EAN: 4043619547050

Country of origin: Taiwan,

Republic of China

Package: Antistatic cover

Specification

Capacity: 8 GB

· Form factor: Mini PCIe - full size

• Interface: SATA 6 Gb/s

Chip: ToshibaFlash type: MLCMaximum channels: 4

Maximum speed: Read 105 MB/s - Write 20 MB/s

Maximum write cycles: 3000

Maximum power consumption: 1.4 W (3.3 V x 433.6 mA)

Thermal sensor: ST- OptionalH/W Write protect: Optional

ATA security: YesS.M.A.R.T.: Yes

Dimensions (LxWxH): 50.8 x 29.8 x 3.3 mm

Vibration: 20G / 7 - 2000Hz
Shock: 1500G / 0,5ms
MTBF: >3 million hours

• Storage temperature: -55°C ~ +95°C

Operation temperature: Industrial Grade -40°C ~ +85°C

System requirements



• A free Mini PCIe (mSATA) slot - full size

Package content

• mSATA memory card