

Delock M.2 SATA 6 Gb/s SSD Industrial 64 GB (S42) Toshiba MLC -40 $^{\circ}$ C \sim 85 $^{\circ}$ C

Description

This flash module by Delok, with a length of 42 mm (2242), is a memory in M.2 format for the SATA interface. It supports the SATA 6 Gb/s specification and convinces with its effective boot time and a lower power consumption than common hard disk drives. The module supports the Delock iSmart function, is stable to vibration and has an extended temperature range from -40°C ~ +85°C. **Delock iSmart** is a powerful and easy-to-use monitoring tool. It allows system integrators to track important disk information, such as temperature, storage space, bad blocks, lifespan and firmware, all under one platform. The intelligent recovery system provides testing and data recovery during voltage fluctuations.



64 GB

Item no. 54783

EAN: 4043619547838

Country of origin: Taiwan,

Republic of China

Package: Antistatic cover

Note

The **Delock iSmart software tool** is available free of charge under the software section.

Specification

Capacity: 64 GB

• Connector: 59 pin M.2 key B+M male

Interface: SATA 6 Gb/sForm factor: M.2 2242

Chip: ToshibaFlash Type: MLCMaximum channel: 2

Maximum speed: read 530 MB/s - write 100 MB/s

Maximum write cycles: 3000

Maximum power consumption: 1.4 W (3.3 V x 422 mA)

Thermal Sensor: yes

H/W Write protect: optional

· ATA security: yes

· iSmart.: yes

Dimensions (LxWxH): 42 x 22 x 3.2 mm

Vibration: 20G @ 7 ~ 2000 Hz

Shock: 1500G @ 0.5 Ms

• MTBF: >3 million hours

• Storage temperature: -55 °C ~ 95 °C

Operation temperature: Industrial grade -40 °C ~ 85 °C



System requirements

• A free M.2 port with key B or key M

Package content

• M.2 module





Interface

M.2 NGFF based on SATA connector:

Technical characteristics

Chipset:	Toshiba
Storage temperature:	-55°C - 95°C
Read:	530 MB/s
Maximum power consumption:	1.4 W
Maximum write cycles:	3000
MTBF:	3 million hours
Interface:	SATA 6.0 Gb/s
Shock:	1500 G @ 0.5 ms
Write:	100 MB/s
Write protect:	optional
Capacity:	64 GB
Thermal sensor:	yes
Vibration:	20 G @ 7 ~ 2000 Hz
Delock iSmart:	Yes

Physical characteristics

Length:	42 mm
Width:	22 mm
Height:	3.2