

Delock M.2 PCIe SSD Toshiba MLC 128 GB (42 mm) -40 °C ~ 85 °C

Description

This flash module by Delock is a memory in M.2 format for the PCIe interface. It supports the PCIe x2 revision 3.0 and convinces with an effective boot time and lower power consumption than common hard disk drives.



Item no. 54822

EAN: 4043619548224

Country of origin: Taiwan,
Republic of China

Package: Antistatic cover

Specification

- Connector: 1 x 59 pin M.2 key B+M male
- Capacity: 128 GB
- Interface: PCIe x2 Rev. 3.0
- Form factor: M.2 2242
- Chipset: Toshiba
- Flash type: MLC
- Channels max.: 4
- Maximum read speed: 1300 MB/s
- Maximum write speed: 190 MB/s
- Maximum write cycles: 3000
- MTBF: 3.000.000 hours
- Power consumption: max. 2.9 W (3.3 V x 880 mA)
- ATA security: no
- Write protection: no
- Thermal sensor: yes
- Vibration: 20G @ 7 ~ 2000 Hz
- Shock: 1500G @ 0.5 ms
- Supports NVM Express (NVMe)

- Dimensions (LxWxH): ca. 42.0 x 22.0 x 4.5 mm
- Storage temperature: -55 °C ~ 95 °C
- Operating temperature: -40 °C ~ 85 °C - industry class

System requirements

- A free M.2 port with key B + M
- M.2 slot with PCIe / NVMe interface

Package content

- M.2 memory

Interface

connector:	1 x 59 pin M.2 key B+M male
------------	-----------------------------

Technical characteristics

Chipset:	Toshiba
Storage temperature:	-55 °C ~ 95 °C
Read:	1300 MB/s
Maximum power consumption:	2,9 W (3,3 V x 880 mA)
Maximum write cycles:	3000
MTBF:	3.000.000 hours
Interface:	PCIe x2 Rev. 3.0
Shock:	1500 G @ 0.5 ms
Write:	190 MB/s
Write protect:	no
Capacity:	128 GB
Thermal sensor:	yes
Vibration:	20 G @ 7 ~ 2000 Hz
Flash type:	MLC

Physical characteristics

Length:	42.0 mm
Width:	22.0 mm
Height:	4.5 mm