
Delock DIMM DDR3L 1 GB 1600 MHz 1.35 V / 1.5 V -40 °C ~ 85 °C Industrial

Description

This DIMM by Delock is suitable for installation in server, industrial PCs and general industrial applications. The memory is ideal for use in harsh environments and has an extended temperature range of -40 ° C ~ 85 ° C. Furthermore it supports an operation with 1.35 V (low voltage) and 1.5 V.



1 GB

Item no. 55841

EAN: 4043619558414

Country of origin: Taiwan, Republic of China

Package: Box

Specification

- Storage capacitiy: 1 GB
- Pin: 240
- Chipset: Micron - Low voltage
- Assembly: 128Mx8
- Frequency: 1600MHz
- Module speed: PC3-12800
- Function: unbuffered - non ECC
- Bandwidth: 64 bit
- Voltage: 1.35 V / 1.5 V
- Operating temperature: -40 °C ~ 85 °C

System requirements

- A free DIMM socket with 240 pin

Package content

- DIMM module

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

Interface

DDR 3:	DIMM

Technical characteristics

Buswidth:	64 bit
Assembly:	128Mx8
Chipset:	Micron
Frequency:	1600 MHz
Operating temperature:	-40 °C ~ 85 °C
Module speed:	PC3 - 12800
Pin:	240
Voltage:	1.35 V 1,5 V
Capacity:	1 GB

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.