

Delock DIMM DDR3L 4 GB 1600 MHz 1.35 V / 1.5 V -40 $^{\circ}$ C \sim 85 $^{\circ}$ C Industrial

Description

This DIMM by Delock is suitable for installation in server, industrial PCs and general industrial applications. The memory is ideal for use in harsh environments and has an extended temperature range of -40 $^{\circ}$ C \sim 85 $^{\circ}$ C. Furthermore it supports an operation with 1.35 V (low voltage) and 1.5 V.



4 GB

Item no. 55843

EAN: 4043619558438 Country of origin: Taiwan, Republic of China

Package: Box

Specification

• Storage capacitiy: 4 GB

• Pin: 240

• Chipset: Micron - Low voltage

Assembly: 512Mx8
Frequency: 1600MHz
Module speed: PC3-12800
Function: unbuffered - non ECC

Bandwidth: 64 bitVoltage: 1.35 V / 1.5 V

• Operating temperature: -40 °C ~ 85 °C

System requirements

• A free DIMM socket with 240 pin

Package content

• DIMM module





Interface

DDR 3: DIMM

Technical characteristics

| Buswidth: | 64 bit |
|------------------------|-----------------|
| Assembly: | 512Mx8 |
| Chipset: | Micron |
| Frequency: | 1600 MHz |
| Operating temperature: | -40 °C ~ 85 °C |
| Module speed: | PC3 - 12800 |
| Pin: | 240 |
| Voltage: | 1.35 V 1,5 V |
| Capacity: | 4 GB |