

Delock Converter Raspberry Pi USB Micro-B female / USB pin header > 2 x USB type A female + 2 x serial RS-232

Description

This converter board by Delock enables you to expand your Raspberry Pi via the Micro USB port or the USB pin header. Thus you will have two USB A ports as well as one D-Sub 9 RS-232 port and one 9 pin pin header for the second RS-232 port.



Item no. 62649

EAN: 4043619626496 Country of origin: Taiwan, Republic of China

Package: White Box

Specification

- Connector:
 - 1 x USB 2.0 type Micro-B female
 - 1 x 5 pin USB 2.0 pin header (4 pins connected)
 - 1 x 2 pin power connector
 - 2 x USB 2.0 type A female
 - 1 x serial RS-232 DB9 male
 - 1 x 9 pin serial RS-232 pin header
- Chipset: Prolific PL2303RA + Renesas D720114
- Data transfer rate: serial up to 230.4 Kb/s USB 2.0 up to 480 Mb/s
- Compliant with OHCI 1.0a and EHCI 0.95
- 2 x jumper for selection of RI or 5 V output for each RS-232 port on pin 9
- 1 x jumper for setting the power supply via USB or 2 pin power connector
- Dimensions (LxWxH): ca. 66 x 64 x 18 mm
- OS independent, no driver installation necessary

DATASHEET



System requirements

- One free USB port
- USB connection cables

Package content

- Converter
- Serial connecting cable
- 4 x screw
- 4 x nut
- 4 x standoff

Images

