Delock M.2 Adapter M.2 > 1 x RJ45 Gigabit LAN ports (USB 3.0)

Description

M.2

This M.2 NGFF module by Delock expands a system by one RJ45 Gigabit LAN port.



Item no. 62683

EAN: 4043619626830

Country of origin: China

Package: Antistatic cover

Specification

- Connector:
  1 x 67 pin M.2 NGFF key B male>
  1 x Gigabit LAN RJ45 female
- Interface: USB 3.0
- Form factor: M.2 NGFF 2260
- Chipset: RTL8153AI
- Maximum power consumption: 1.45 W (3.3 V, 440 mA)
- Vibration: 5G @7 ~ 2000Hz
- Shock: 50G @0.5 ms
- Storage temperature: -55°C ~ +95°C
- Operation temperature: 0°C ~ +70°C
- Dimensions (LxWxH): ca. 60.0 x 22.0 x 6.1 mm
- Needs CDC-ECM for Linux support

System requirements

- Windows 7/7-64/8/8-64/8.1/8.1-64/10/10-64, Linux Kernel 3.x
- A free M.2 NGFF Key B slot with 60 mm up to 110 mm
- M.2 slot with USB interface

Package content

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

- M.2 NGFF module
- Daughter Board
- Connection cable 32 cm
- Slot bracket

Images





© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

General

Form factor:	M.2 2260
Supported operating system:	Needs Linux CDC-ECM support Linux Kernel 3.x Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8 32-bit Windows 8 64-bit Windows 8.1 32-Bit Windows 8.1 64-Bit Windows XP 32-bit Windows XP 64-bit
Storage temperature range:	-55 °C ~ 95 °C

Interface

connector:	M.2 NGFF on USB basis
Connector 1:	1 x RJ45 Gigabit LAN

Technical characteristics

Operating temperature:	0 °C ~ 70 °C
Shock:	50 G @ 0.5 ms
Current consumption:	440 mA
Vibration:	5 G @ 7 ~ 2000 Hz

Physical characteristics

Length:	60 mm
Width:	22 mm
Height:	6.1 mm

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.