

Delock Slim SATA 5.25" Installation Frame (13 mm) for 1 x M.2 SSD Key B

Description

This Delock installation frame in slim-format can be installed into a 5.25" SATA slim bay in order to operate a M.2 SSD.



Item no. 62716

EAN: 4043619627165 Country of origin: China Package: Retail Box

Specification

- · Connector:
- 1 x 67 Pin M.2 key B slot
- 1 x Slim SATA 13 pin female
- For the installation into a slim 5.25" bay
- Interface: SATA
- Supports M.2 modules in format 2280, 2260 and 2242 with key B or key B+M based on SATA
- Maximum height of the components on the module: 1.5 mm application of double-sided assembled modules supported
- Data transfer rate up to 6 Gb/s
- Dimensions (LxWxH): ca. 128 x 128 x 13 mm
- OS independent, no driver installation necessary

System requirements

• A free slim SATA 5.25" bay

Package content

- Slim SATA 5.25" installation frame
- Screwdriver



• Spacer

Images











General

| Form factor: | Slim 5.25" |
|---|---|
| Supported operating system: | OS independent, no driver installation necessary |
| Slot: | SATA |
| Supported module: | M.2 modules in format 2280, 2260, 2242 and 2230 with key B or key B+M based on SATA |
| Maximum height of the components on the module: | 1.5 mm application of double-sided assembled modules supported |

Interface

| Connector 1: | 1 x Slim SATA 13 pin receptacle |
|--------------|---------------------------------|
| Connector 2: | 1 x 67 pin M.2 key B slot |

Technical characteristics

| Data transfer rate: | 6 Gb/s |
|---------------------|--------|
|---------------------|--------|

Physical characteristics

| Length: | 128 mm |
|---------|--------|
| Width: | 128 mm |
| Height: | 13 mm |