

Delock Converter SCART / HDMI to HDMI with Scaler

Description

The Delock A/V converter converts an analogue SCART video and audio signal to a digital HDMI signal. Thereby e.g. a VCR or game console can be connected to an HDMI monitor or Full HD TV. In addition, an HDMI input is present, so that the converter can be used as a switch. Both inputs can be scaled via the integrated video processor to an HDMI output signal of 720p or 1080p with 50 or 60 Hz. The audio signal is simultaneously available at the HDMI output, as a digital S/PDIF signal and as analogue signal at the stereo jack.



Item no. 62783

EAN: 4043619627837 Country of origin: China

Package: Box

Specification

• Connectors:

Input:

1 x SCART female (RGB or Composite)

1 x HDMI-A 19 pin female

1 x DC 5 V power connector

Output:

1 x HDMI-A 19 pin female

1 x 3.5 mm 3 pin stereo jack female

1 x Coaxial female S/PDIF

- Input switchable between SCART / HDMI
- Output switchable between 720p / 1080p, PAL / NTSC
- Resolution (SCART input) PAL / NTSC-M / NTSC 4.43 / SECAM / PAL-M / PAL-N
- Resolution (HDMI output) 1280 x 720 or 1920 x 1080 @ 50 or 60 Hz
- Supports stereo audio
- Dimensions (LxWxH): ca. 102 x 101 x 25 mm

Power supply specification

• Wall power supply





• Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A

• Output: 5 V / 1 A

• Ground outside, plus inside

• Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9.5 mm

System requirements

- Monitor or TV with HDMI connector
- Connection cables

Package content

- Converter SCART / HDMI > HDMI
- External power supply
- User manual

Images







General

Specification: High Speed HDMI

Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 1 x HDMI-A female 1 x Coaxial female S/PDIF
Input:	1 x HDMI-A female 1 x 5 V DC female 5,5 mm x 2,1 mm 1 x SCART female

Technical characteristics

Maximum screen resolution: 1920 x 1080 @ 60 Hz

Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	102 mm
Width:	101 mm
Height:	25 mm

Power supply

Type:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.2 A
Output:	5 V / 1 A
Connector:	DC male 5.5 mm x 2.1 mm
Cable length:	1 m