

# Delock Adapter USB Type-C™ male > HDMI female (DP Alt Mode) 4K 30 Hz + USB Type-A + USB Type-C™ PD

#### Description

This adapter by Delock is suitable for the connection of a HDMI monitor to a computer with USB-CTM interface and DisplayPort alternate mode support. Thus, the adapter can be connected to different laptops like MacBook, Chromebook and similar. In addition, the adapter can also be operated on a ThunderboltTM 3 interface. Additional the adapter has a USB 3.1 Type-A port and a USB-CTM port. The USB-CTM port can be used for power supply of the output device or to transfer data in USB 2.0 speed. Different USB devices such as docking stations, card reader, external enclosure etc. can be connected.



#### Item no. 62991

EAN: 4043619629916 Country of origin: China Package: Retail Box

#### **Specification**

- · Connectors:
  - 1 x SuperSpeed USB (USB 3.1 Gen 1) USB Type-C™ male >
  - 1 x HDMI-A 19 pin female
  - 1 x SuperSpeed USB (USB 3.1 Gen 1) Type-A female
  - 1 x USB Type-C<sup>™</sup> 2.0 Power Delivery female (optional for power supply)
- Chipset: VIA VL101 + VL813 + Parade PS176
- DisplayPort 1.2 and High Speed HDMI with Ethernet (HEC) specification
- Resolution up to 3840 x 2160 @ 30 Hz
   (depending on the system and the connected hardware)
- · Transmission of audio and video signals
- · Supports 3D displays
- Supports HDCP 1.3
- USB bus powered
- Plug & Play
- · Connectors: gold-plated
- 1 x ferrite core
- Metal housing



- Cable length without connectors: ca. 20 cm
- · Colour: grey

## **System requirements**

- Linux Kernel 4.3 or above
- Mac OS 10.12 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- Windows 10 Mobile
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

## **Package content**

USB-C<sup>™</sup> to HDMI Adapter + USB Type-A

# **Images**









#### General

Function:	Plug & Play
Specification:	DisplayPort 1.2 High Speed HDMI with Ethernet HDCP 1.3
Supported operating system:	Linux Kernel 4.3 or above Linux Kernel 4.9 or above Mac OS 10.12 or above Windows 10 32-Bit Windows 10 64-Bit Windows 10 Mobile Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

## Interface

Output:	1 x HDMI-A female 1 x USB 5 Gbps Type-A female
Input:	1 x USB Type-C <sup>™</sup> female (power supply) 1 x USB Type-C <sup>™</sup> male

#### **Technical characteristics**

Maximum screen resolution:	3840 x 2160 @ 30 Hz
Signal transmission:	video audio

# **Physical characteristics**

Ferrite core:	1 x
Housing material:	Aluminium
Cable length:	20 cm