Delock HDMI Audio Extractor 4K 60 Hz compact

Description

This adapter by Delock can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) or analogue (stereo) to other devices, such as headphones or a surround receiver.

Item no. 63276

EAN: 4043619632763
Country of origin: China
Package: Retail Box

Specification

- Connectors:
  Input:
  1 x HDMI-A 19 pin male
  1 x USB Type Micro-B female (5 V power supply)
  Output:
  1 x HDMI-A 19 pin female
  1 x 3.5 mm 3 pin stereo jack female (audio)
  1 x TOSLINK female S/PDIF
- High Speed HDMI, 3D and HDCP 1.4 / HDCP 2.2
- Supports HDR (High Dynamic Range)
- Automatic switching to stereo (2.0) when using the stereo jack and automatic muting of the digital output
- Resolution up to 3840 x 2160 @ 60 Hz
- Video bandwidth up to 600 MHz / 6 Gbps, max. 18 Gb/s
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)
- HDMI audio routed to the output (pass-through)
- Power consumption: max. 2 W

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

System requirements

- A free HDMI-A female
- A free USB Type-A female port

Package content

- HDMI Audio Extractor
- USB Type-A to Type Micro-B cable, length ca. 30 cm
- User manual

Images





General

Specification:	DTS Audio High Speed HDMI Dolby Digital HDCP 1.4 HDCP 2.2 LPCM HDR

Interface

Output:	1 x 3.5 mm 3 pin stereo jack female 1 x HDMI-A female 1 x TOSLINK female
Input:	1 x HDMI-A male 1 x USB 2.0 Type Micro-B female

Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz
Video bandwidth:	600 MHz / 6 Gbps

Physical characteristics

Housing colour:	black
Housing material:	Plastic

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.