

Delock 3.5" USB 3.2 Gen 1 Front Panel 2 x USB Type-C™ + 2 x USB Type-A

Description

This front panel by Delock can be installed into a free 3.5" bay of a computer. It has two USB 3.2 Gen 1 Type-A and two USB 3.2 Gen 1 Type-C ports. It will be connected to the motherboard internally via a pin header male port.



Item no. 64049

EAN: 4043619640492 Country of origin: China Package: Retail Box

Specification

Connectors:

external:

2 x SuperSpeed USB (USB 3.2 Gen 1) USB Type-C™ female

2 x SuperSpeed USB (USB 3.2 Gen 1) Type-A female internal:

1 x 19 pin USB 3.0 pin header female port on the cable

- 1 x 4 pin power connector
- Chipset: Genesys Logic GL3523
- Data transfer rate up to:

SuperSpeed 5 Gbps,

Hi-Speed 480 Mbps,

Full-Speed 12 Mbps,

Low-Speed 1.5 Mbps

- · Cable data:
 - 1 x 19 pin USB 3.0 pin header female cable, length ca. 54 cm (without connectors)
 - 1 x power cable 4 pin female to 1 x SATA 15 pin plug,

length ca. 17 cm (without connectors)

- 3.5" metal frame
- Colour: black





• Hot Swap, Plug & Play

System requirements

- Linux Kernel 3.3 or above
- Windows 8.1/8.1-64/10/10-64
- PC with one free 3.5" bay
- Motherboard with a free 19 pin USB 3.0 pin header male
- Power supply with SATA 15 pin receptacle

Package content

- 3.5" front panel
- USB 3.0 pin header female cable
- Power cable
- Screws
- User manual

Images











General

Form factor:	3.5"
Function:	Hot Swap Plug & Play
Supported operating system:	Linux Kernel 3.3 or above Windows 10 64-Bit Windows 8.1 64-Bit

Interface

External:	2 x USB Type-C [™] female 2 x USB 5 Gbps Type-A female
Internal:	1 x 19 pin USB 5 Gbps pin header female 1 x 4 pin power connector

Technical characteristics

Chipset:	Genesys Logic GL3520
Data transfer rate:	USB 5 Gbps up to 5 Gb/s

Physical characteristics

Housing material:	metal
Length:	102 mm
Width:	95 mm
Height:	26 mm
Colour:	black