

Delock SuperSpeed USB 5 Gbps Docking Station for 4 x SATA HDD / SSD with Clone Function

Description

This HDD / SSD Docking Station in by Delock enables an external connection of up to **four 2.5" or 3.5" SATA HDDs / SSDs** through the USB interface, as well as the simple exchange of the drives by **Hot Swap**.

It is also possible to connect a single hard disk to the computer by using the **eSATA** connector.

Four bays for HDD / SSD with clone function

Up to four HDDs or SSDs can be inserted and accessed simultaneously.

The **clone function** enables to copy the content of one HDD / SSD to one or more others without using a PC.

USB Type-C™ connection and separate power supply

Due to the USB port and the included USB cable, the docking station can easily be connected to the computer. In addition, the power supply included in the delivery content ensures a supply for the storage devices used.



Item no. 64063

EAN: 4043619640638

Country of origin: China

Package: Retail Box

Specification

- Connectors:
 - 4 x SATA 22 pin receptacle
 - 1 x SuperSpeed USB 5 Gbps (USB 3.2 Gen 1) Type-B female
 - 1 x eSATA 7 pin plug
 - 1 x DC jack
- Chipset: Genesys Logic GL3523, JMicron JMS578
- Function key:
 - 1 x Clone button
 - 1 x On / Off switch
- For 2.5" and 3.5" SATA HDD / SSD
- Suitable for all SATA HDDs / SSDs up to SATA 6 Gb/s
- Data transfer rate up to 3 Gb/s
- 5 x LED indicator

- LED indicator for power, access and copy status
- Bootable (eSATA)
- Dimensions (LxWxH): ca. 166 x 127 x 65 mm
- Hot Swap, Plug & Play

Power supply specification

- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 2 A
- Output: 12 V / 6.5 A
- Ground outside, plus inside
- Dimensions:
 - inside: \varnothing ca. 2.1 mm
 - outside: \varnothing ca. 5.5 mm
 - length: ca. 10 mm

System requirements

- Chrome OS
- Linux Kernel 3.17 or above
- Mac OS 10.14.2 or above
- Windows 7/7-64/8.1/8.1-64/10/10-64
- PC or laptop with a free USB Type-A port

Package content

- Docking station
- 1 x cable USB 3.0 A male to USB 3.0 B male, length ca. 80 cm
- External power supply
- User manual

Images



General

Function:	Hot Swap Plug & Play bootable Clone Function
Suitable for data medium:	2.5" 3.5" SSD or HDD
Supported operating system:	Chrome OS Linux Kernel 3.17 or above Mac OS 10.14.2 or above Windows 10 32-Bit Windows 10 64-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	1 x DC 12 V power connector 1 x eSATA 6 Gb/s 7 pin plug 1 x USB 5 Gbps Type-B female
Internal:	4 x SATA 6 Gb/s 22 pin receptacle

Technical characteristics

Chipset:	Genesys Logic GL3523 JMicron JMS578
Data transfer rate:	5 Gbps

Physical characteristics

Housing material:	Plastic
Length:	166 mm
Width:	127 mm

Height:	65 mm
Colour:	black