

Delock Dual HDMI Adapter with 4K 60 Hz and PD 3.0 for MacBook

Description

This adapter by Delock can be connected to a MacBook with two adjacent ThunderboltTM 3 ports, e.g. the MacBook Pro. **Two monitors** can be operated at the HDMI outputs with **4K 60 Hz simultaneously**.

USB Power Delivery (USB PD 3.0) support up to 100 watt

The adapter has a USB Type-CTM Power Delivery port to connect the power supply of the laptop to charge it. The adapter can also be used without a power supply.

Small sturdy helper

Due to its **small dimensions and its sturdy housing**, this Delock adapter is particularly suitable for travelling. It can simply be packed into the bag together with the laptop and used as needed.

Note

Only one additional external monitor can be connected to MacBook devices with M1 chipset.



Item no. 64123

EAN: 4043619641239 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - 2 x USB Type-CTM male
 - 2 x HDMI-A female
 - 1 x USB Type-CTM female (power supply)
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected hardware)
- Transmission of audio and video signals
- Functions: Mirrored or Extended
- USB Power Delivery (PD) 3.0
- Metal housing
- Rubberized bottom
- · Colour: grey





• Dimensions (LxWxH): ca. 62 x 40 x 11 mm

System requirements

MacBook Pro with two adjacent Thunderbolt™ 3 ports

Package content

- Adapter
- User manual

Images











Interface

Connector 1:	2 x USB Type-C™ male
Connector 2:	2 x HDMI-A female
connector 3:	1 x USB Type-C™ Power Delivery female

Technical characteristics

Maximum screen resolution: 3840 x 2160 @ 60 Hz

Physical characteristics

Housing material:	metal
Colour:	grey