

Delock SMA Jack 90° PCB Thread length 16 mm

Description

This jack by Delock is suitable for soldering on circuit boards. The gold coating prevents corrosion and ensures an optimal connection.



Item no. 65848

EAN: 4043619658480

Country of origin: China

Package: Zip poly bag

Specification

- Connector: 1 x SMA Jack 90°
- Pin: Brass gold plated
- Insulator: PTFE
- Housing: Brass gold plated
- Frequency range: 0 - 6 GHz
- Impedance: 50 Ohm
- VSWR: 1.5
- Thread type: 1/4" - 36 UNS - 2A
- Thread length: 16 mm
- Operating temperature: -55 °C ~ 165 °C
- Withstand Voltage: 500V / 50Hz
- Soldering: 5 solder joint
- Dimensions (LxHxD): 22.0 x 12.0 x 4.6 mm


System requirements

- Suitable board for mounting the SMA connector

Package content

- SMA Jack

Images



General

Mounting type:	Soldering
----------------	-----------

Interface

connector:	1 x SMA Jack 90°
------------	------------------

Technical characteristics

Frequency range:	0 - 6 GHz
Impedance:	50 Ω
Operating temperature:	-55 °C ~ 165 °C
VSWR:	1.2

Physical characteristics

Solder pin:	Ø 0.95 mm
Housing material:	brass gold plated
Diameter:	4.6 mm
Length:	22.0 mm
Height:	12.0 mm
Thread type:	1/4" - 36 UNS - 2A
Insulator:	PTFE