

# **Delock HDMI Receiver for Video over IP**

### **Description**

This video extender system by Delock allows video signals to be transmitted over an IP network. The transmitter and receiver can be connected with a network cable of up to 100 m. Alternatively both devices can be connected via a switch, the distance between the source and the display device can then be 200 m.

#### **HDBitT**

The HDBitT technology allows different transmitters and receivers to be combined with each other, e.g. a DisplayPort transmitter with an HDMI receiver. Optionally, several receivers can be operated simultaneously.

#### Item no. 65951

EAN: 4043619659517 Country of origin: China Package: White Box

## **Specification**

- Connectors:
  - 1 x RJ45 jack
  - 1 x HDMI-A 19 pin female
  - 1 x 3.5 mm 3 pin stereo jack female (IR)
  - 1 x DC 5.5 x 2.1 mm female
- · Transmission of audio and video signals
- Transmission of IR signals 20 60 kHz
- Supported resolution: 480i / 480p / 576i / 576p / 720p / 1080i / 1080p
- Supports EDID und HDCP
- Supports RTP Multicast
- Supports One-to-one and One-to-many connections
- Latency: ca. 400 ms
- Power consumption: max. 3.5 W
- · Robust metal housing
- Wallmount option
- Dimensions (LxWxH): ca. 97 x 94 x 24 mm

## Power supply specification



- · Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.2 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 9 mm

# **System requirements**

- Connection cables
- Transmitter for Video over IP
- Switch with VLAN or IGMP snooping

# Package content

- HDMI receiver
- · Infrared receiver
- Power supply
- User manual

## **Images**











#### General

|--|

#### Interface

connector:	1 x RJ45 jack
Connector 1:	1 x HDMI-A female
connector 3:	1 x DC jack
connector 4:	1 x 3.5 mm 3 pin stereo jack female

## **Technical characteristics**

# **Physical characteristics**

Housing colour:	black
Housing material:	metal