

# Delock HDMI Switch 3 x HDMI in to 1 x HDMI out 4K 60 Hz with Audio Extractor

## Description

With this HDMI switch by Delock up to **three HDMI devices** can be used with one HDMI monitor, TV or projector. The button on the device or the remote control can be used to switch between the HDMI devices.

### Audio extractor

This function can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent **digital (S/PDIF) or analogue (stereo)** to other devices, such as headphones or a surround receiver.

### Audio Return Channel (ARC)

ARC can be enabled at the push of a button on the device or the remote control. Then the **audio signal of the connected TV** device is routed to the S/PDIF connectors of the switch.



**Item no. 66498**

EAN: 4043619664986

Country of origin: China

Package: Retail Box

## Specification

- Connectors:  
Input:  
3 x HDMI-A female  
1 x DC 5 V power connector  
Output:  
1 x HDMI-A female  
2 x RCA female (audio)  
1 x TOSLINK female S/PDIF  
1 x RCA female S/PDIF
- HDMI port switching: automatic function, via button or via infrared remote control
- LED indicators for active HDMI port
- High Speed HDMI specification
- Supports 3D displays
- Supports HDCP 1.4 and 2.2
- Supports HDR
- Resolution up to 3840 x 2160 @ 60 Hz (depending on the system and the connected

hardware)

- Video bandwidth up to 600 MHz / 6 Gbps, max. 18 Gbps
- Power consumption: max. 5 W
- Metal housing
- Removable wallmount brackets
- Colour: black
- Dimensions (LxWxH): ca. 168 x 75 x 21 mm

---

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
  - inside: ø ca. 2.1 mm
  - outside: ø ca. 5.5 mm
  - length: ca. 9 mm

---

## System requirements

- A free HDMI female
- HDMI cable

---

## Package content

- HDMI switch
- Remote control
- Mounting brackets and screws
- USB power cable, length: ca. 0.5 m
- Power supply
- User manual

## Images



## General

Specification:	High Speed HDMI HDCP 1.4 HDCP 2.2 HDR
----------------	--

## Interface

Output:	1 x RCA female 1 x HDMI-A female 1 x TOSLINK female S/PDIF 2 x RCA female (red, white)
Input:	1 x 5 V DC female 5,5 mm x 2,1 mm 3 x HDMI-A female

## Technical characteristics

Maximum screen resolution:	3840 x 2160 @ 60 Hz
----------------------------	---------------------

## Physical characteristics

Housing colour:	black
Housing material:	metal
Length:	168 mm
Width:	75 mm
Height:	21 mm

## Power supply

Type:	Euro wall power supply
Input:	AC 100 - 240 V / 50 - 60 Hz / 0.5 A
Output:	5 V / 1 A
Connector:	DC male 5.5 mm x 2.1 mm