

Delock USB Type-C™ Splitter (DP Alt Mode) > 2 x HDMI out 4K 30 Hz

Description

This splitter by Delock is suitable for the connection of two HDMI monitors to a computer with USB-CTM interface and DisplayPort alternate mode support. Two monitors can be operated simultaneously at the outputs.



The product is a Multi-Stream-Transport (MST) hub and supports the extended desktop configuration of Displayport 1.2. When Mac OS is used, the same image is displayed on both ports (mirrored), it is not possible to use both ports independently of each other.



Item no. 87715

EAN: 4043619877157 Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

• Connectors:

Input: 1 x USB Type-C™ male Output: 2 x HDMI-A 19 pin female

• Chipset: STDP4320

• DisplayPort 1.2 specification

- Resolution up to 2560 x 1440 @ 60 Hz / 3840 x 2160 @ 30 Hz (depending on the system and the connected hardware)
- Active converter, Single / Multi Stream Transport Hub (SST / MST)
- Functions: Mirrored or Extended (Windows only)
- Transfer of audio and video signals
- · USB bus powered
- Metal housing
- · Colour: silver
- Cable length incl. connectors: ca. 10 cm
- Dimensions (LxWxH): ca. 73 x 60 x 15 mm

System requirements





- Windows 8.1/8.1-64/10/10-64, Mac ex OS 10.9
- PC or laptop with a free USB Type-C™ port and DisplayPort alternate mode or
- PC or laptop with a free Thunderbolt™ 3 port

Package content

- USB-CTM Splitter (DP Alt Mode)
- User manual

Images







General

Specification:	DisplayPort 1.2
Supported operating system:	Mac OS 10.9 or above Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

Output:	2 x HDMI-A female
Input:	1 x USB Type-C™ male

Technical characteristics

Chipset:	STDP4320
Maximum screen resolution:	3840 x 2160 @ 30 Hz

Physical characteristics

Housing colour:	silver
Housing material:	metal
Cable length incl. connector:	10 cm
Length:	73 mm
Width:	60 mm
Height:	15 mm