

Delock WLAN 802.11 b/g/n Antenna RP-SMA plug 5 dBi omnidirectional with tilt joint black

Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.



Item no. 88396

EAN: 4043619883967 Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

• Connector: RP-SMA plug

• Frequency range: 2.400 - 2.500 GHz

Antenna gain: 5 dBiImpedance: 50 Ohm

· Polarisation: linear, vertical

• VSWR: 2.0

• Operating temperature: -10 °C ~ 55 °C

· Housing material: ABS

· Colour: black

• Length:

ca. 200.30 mm (with tilt joint) ca. 167.80 mm (without tilt joint)

• Diameter:

ca. 6.00 mm (top)

ca. 13.20 mm (RP-SMA)

System requirements



• Device with a free RP-SMA jack

Package content

• WLAN antenna

Images







Interface

connector:	RP-SMA plug	

Technical characteristics

Frequency range:	2.400 - 2.500 GHz
Gain:	5 dBi
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
Polarisation:	linear vertical
VSWR:	2.0

Physical characteristics

Housing material:	ABS
Diameter connector:	13.20 mm
Length with tilt joint:	200.30 mm
Length without tilt joint:	167.80 mm
Colour:	black