

Delock WLAN 802.11 ac/a/b/g/n Antenna RP-SMA plug 2 - 5 dBi omnidirectional with tilt joint white

Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.

Bluetooth



RP-SMA

Item no. 88460

EAN: 4043619884605

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Specification

- Connector: RP-SMA plug
- Frequency range:
2.400 - 2.500 GHz
5.100 - 5.875 GHz
- Antenna gain:
2 dBi @ 2.5 GHz
5 dBi @ 5.7 GHz
- Impedance: 50 Ohm
- Polarisation: linear, vertical
- VSWR: 2.0
- Operating temperature: -10 °C ~ 55 °C
- Housing material: ABS
- Colour: white
- Length:
ca. 143.00 mm (with tilt joint)
ca. 109.70 mm (without tilt joint)
- Diameter:
ca. 18.80 mm (top)

ca. 10.00 mm (RP-SMA)


System requirements

- Device with a free RP-SMA jack

Package content

- WLAN antenna

Images



Interface

connector:	RP-SMA plug
------------	-------------

Technical characteristics

Frequency range:	2.400 GHz - 2.500 GHz 5.100 - 5.875 GHz
Gain:	2 dBi @ 2.5 GHz 5 dBi @ 5.7 GHz
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
Polarisation:	linear vertical
VSWR:	2.0

Physical characteristics

Housing material:	ABS
Diameter connector:	10.00 mm
Length with tilt joint:	143.00 mm
Length without tilt joint:	109.70 mm
Colour:	white