



Delock WLAN 802.11 ac/a/h/b/g/n Antenna RP-SMA plug 5.5 - 9 dBi omnidirectional with tilt joint black

Description

This Wireless LAN antenna can be connected to a WLAN device with RP-SMA interface, in order to send and receive signals.



Item no. 88991

EAN: 4043619889914 Country of origin: Taiwan, Republic of China

Package: Retail Box

Specification

• Connector: RP-SMA plug

• Frequency range:

2.400 - 2.500 GHz

5.150 - 5.875 GHz

Antenna gain:

5.5 dBi @ 2.400 - 2.500 GHz 9.0 dBi @ 5.150 - 5.875 GHz

• Impedance: 50 Ohm

· Polarisation: linear, vertical

• VSWR: 2.0

• Operating temperature: -10 °C ~ 55 °C

· Housing material: ABS

· Colour: black

• Length:

ca. 296.10 mm (with tilt joint) ca. 245.00 mm (without tilt joint)

• Diameter:

ca. 28.00 mm (max.)





ca. 13.00 mm (RP-SMA)

System requirements


• Device with a free RP-SMA jack


Package content


• WLAN antenna


Images















Interface

RP-SMA plug connector:

Technical characteristics

Frequency range: 2.400 - 2.500 GHz 5.1500 GHz - 5.8750 GHz Gain: 5.5 dBi @ 2.400 - 2.500 GHz 9.0 dBi @ 5.150 - 5.875 GHz Impedance: 50Ω Operating temperature: -10 °C ~ 55 °C Polarisation: linear vertical VSWR: 2.0

Physical characteristics

Housing material:	ABS
Diameter:	28.00 mm
Diameter connector:	13 mm
Length with tilt joint:	296.10 mm
Length without tilt joint:	245.00 mm
Colour:	black