
Delock PCI Express Card > 2 x internal SATA 6 Gb/s + 1 x internal IDE

Description

The Delock PCI Express card expands your PC by two internal SATA ports, as well as one internal IDE port. You can connect devices like e.g. hard drives, DVD-drives etc. to the card.



Item no. 89293

EAN: 4043619892938

Country of origin: China

Package: Retail Box

Specification

- Connector:
  internal:
  2 x SATA 6 Gb/s 7 pin female
  1 x IDE 40 pin male
  1 x PCI Express x1, V2.0
  1 x pin header for PWR LED for indication of hard drive accessing
- Chipset: Marvell
- Data transfer rate:
  SATA up to 6 Gb/s
  PATA up to 133 Mb/s
  PCI Express x1 up to 5 Gb/s
- Supports SATA Port Multiplier
- Supports hard drive with Native Command Queue (NCQ) feature
- Supports ATA, ATAPI-7
- Supports PIO and DMA modes
- Supports IDE Master and Slave operation
- Supports Raid 0, 1 on SATA drives
- Hot Plug

© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.

System requirements

- Windows Vista/Vista-64/7/7-64/8/8-64/8.1/8.1-64/10/10-64, Linux Kernel 3.7
- PC with one free PCI Express slot

Package content

- PCI Express card
- Low profile bracket
- LED cable
- Driver CD
- User manual

Images



© 2024 by Delock. All names and symbols mentioned here are property of the respective producer.
Printing errors, changes and errors excepted.