

Delock LTE Antenna SMA plug 2 dBi omnidirectional rotatable with tilt joint black

Description

This LTE antenna by Delock allows the usage of different LTE bands inside. It is completely compatible to GSM, UMTS, Bluetooth, WLAN 2.4 GHz, ZigBee, DECT, Z-Wave and LoRa 868 MHz / 915 MHz.



Item no. 89604

EAN: 4043619896042

Country of origin: Taiwan,
Republic of China

Package: Retail Box

Specification

- Connector: 1 x SMA plug
- Frequency range:
698 - 960 MHz
1710 - 2690 MHz
- GSM, UMTS, Bluetooth, WLAN 2.4 GHz, ZigBee, DECT, Z-Wave, LoRa 868 MHz / 915 MHz
- Antenna gain: 2 dBi
- Impedance: 50 Ohm
- VSWR: 4.5 (698 - 960 MHz) ; 3.5 (1710 - 2690 MHz)
- Polarisation: linear, vertical
- Operating temperature: -20 °C ~ 65 °C
- Housing material: ABS
- Colour: black
- Dimensions (LxWxH): ca. 20.5 x 4.3 x 1.4 cm


System requirements

- Device with a free SMA jack

Package content

- Antenna

Images



General

Suitable for indoor:	yes
----------------------	-----

Interface

connector:	1 x SMA plug
------------	--------------

Technical characteristics

Frequency range:	1710 - 2690 MHz 694 - 960 MHz
Antenna gain:	2 dBi
Impedance:	50 Ω
Operating temperature:	-20 °C ~ 65 °C
Polarisation:	linear vertical
VSWR:	3.5 - 4.0

Physical characteristics

Housing material:	ABS
Diameter connector:	1.4 cm
Length with tilt joint:	20.5 cm