

# Delock 3G-SDI Splitter 1 in > 4 out

## Description

This SDI splitter by Delock can be used to receive signals of one SDI input source, such as a DVR, an HD-SDI camera or other SDI device, to up to 4 different output devices such as SDI monitors.



**Item no. 93250**

EAN: 4043619932504

Country of origin: China

Package: White Box

## Specification

- Connectors:  
Input:  
1 x BNC female (3G-SDI)  
1 x 5 V DC jack  
Output:  
4 x BNC female (3G-SDI)
- Supported resolution:  
SD 480i, 525i and 625i  
HD 720p 24, 25, 30, 50 and 60 Hz  
HD 1080i 50, 60 Hz  
HD 1080p 24, 25, 30, 50 and 60 Hz
- Robust metal housing
- Power consumption: max. 1.2 W
- Dimensions (LxWxH): ca. 162 x 82 x 25 mm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A

- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:  
inside:  $\varnothing$  ca. 2.1 mm  
outside:  $\varnothing$  ca. 5.5 mm  
length: ca. 9 mm

## Package content

- 3G-SDI splitter
- Power supply

## Images

