


P1

EAN: 4043619829781



ELECTRICAL PROPERTIES:

1. 100% OPEN SHORT MIS-WIRE TEST
2. Contact Resistance:10ohm
3. Insulation Resistance:5Mega ohm
4. Hipot test:300V/10ms.



PIN ASSEMBLY

P1	P2
1 GND	1
2 A+	2
3 A-	3
4 GND	4
5 B-	5
6 B+	6
7 GND	7

P1	P3
1 RED(PWR)	1 WHITE(UTP_D-)
2 WHITE(UTP_D-)	2 GREEN(UTP_D+)
3 GREEN(UTP_D+)	3 YELLOW(SDP1+)
4 YELLOW(SDP1+)	4 BLUE(SDP1-)
5 BLUE(SDP1-)	5 DRAIN(SDP1_Drain)
6 DRAIN(SDP1_Drain)	6 PURPLE(SDP2+)
7 PURPLE(SDP2+)	7 Braid
8 Braid	
9	
10	



7	UL20276 CIP#28#*D+AL+MYAL1)*2C+IP#28#*2C*28#*AL+B DD5.5mm BLUE IN COLOR	PCS	1
6	HOUSING 20P PH2.0MM BLUE IN COLOR	PCS	1
5	SSP PVC MOLDING BLUE IN COLOR		
4	SSP PVC MOLDING BLACK IN COLOR		
3	SATA 7P CABLE SIDE CONTACTIG/F	PCS	1
2	USB3.0+ESATA CONN PCB SIDE SHELL PLATEDNICEKL CONTACTIG/F	PCS	1
1	UL30#*/2PR+24#*/2C+AB TPR BLACK DD5.8mm	PCS	1
No.	Part Name	Quantity	

Date	2011 / 08 / 15
Unit	mm
Projection	A
Rev	A

Title: Slot bracket 1x Multiport ext. 1x USB 3.0 pin header + SATA int.	
Item no.	82978
Barcode	4043619829781
File No.	87715