



Specifications :

Material :

1. Panel : SECC, 1.2 mm thickness with optional color painted.
- Identification :
 - 2-1. I.D. Plate : PVC, Transparent color.
 - 2-2. Paper.
 - 2-3. I.D. Bracket : ABS, UL 94V-0.
- RJ45 Jack :
 - 3-1. Housing : PBT+Glass Fiber, UL 94V-0.
 - 3-2. Contact Bracket : PBT+Glass Fiber, UL 94V-0.
- RJ45 Jack Contact :
 - 4-1. Material : Phosphor Bronze with Nickel plated.
 - 4-2. Finish : 50 micro-inch Gold plated on Plug contact area.
- RJ45 Jack Shield : Bronze With Nickel plated.
- Dust Cover : Polycarbonate, UL 94V-2.
- IDC :
 - 7-1. Housing : PC+Glass Fiber, UL 94V-2.
 - 7-2. Terminal : Phosphor Bronze with Tin plated.
- Ground Wire : 18 AWG Wire, with Green/Yellow striped color.
- PCB : FR4, UL 94V-0.

Performance :

- T568A & T568B wiring sticker on PCB.
- Insertion force : 30N max. (IEC 60603-7-5)
- Retention strength : 7.7 kg between Jack and Plug.
- Operating temperature : -10°C to 60°C. (ISO/IEC 11801, ANSI/TIA/EIA568 B.2)
- Life(mating cycles) :
 - *Jack : 750 cycles min. (ISO/IEC 11801, IEC 60603-7-5)
 - *IDC : Suitable for 22-26 AWG stranded and solid wire, Compatible with Krone punch down tool.
- The 10G channel transmission performance is in compliance with TIA/EIA 568B.2-10 10G & ISO/IEC 11801 standard.



Date	2015 / 09 / 11	Title:	19 Patch Panel 24 Port Cat6A
Unit	mm	Item no.	43319
Projection		Barcode	4043619433193
Rev	A	File No.	