





REV	ECRN	DATE
1	NEW PRODUCTION	20150506
2	NEW PRODUCTION	20180319




TTL-PCB

TOP



1 2 3

BOTTOM



4 5 6

PIN WIRING

P1		P2
1	RED (5V)	(VCC)
2	ORANGE	(TXD)
3	YELLOW	(RXD)
4	GREEN	(RTS#)
5	BLACK	(GND)
6	BROWN	(CTS#)

模具编号：P-38

NOTES:

- 1.ELECTRICAL TEST:100%OPEN,SHORT&MIS WIRE TEST.
- 2.CONTACT RESISTANCE:0.5ohm,
- 3.INSULATOR RESISTANCE:5M ohm.
- 4.HIGH VOLTAGE:DC 300V 0.01sec.
- 5.MUST BE ROHS COMPLIANT.

⑧	I.180150.0301R	PE BAG	180*150*0.04MM PE袋 PRINTED BLACK FONT" USB Cable w/FTDI set to 5V"	1	PCS
⑦	F.0501B0.0100R	TUBE	φ5.5*20mm HEAT TUBE COLOR BLACK	1	PCS
⑥	I.000001.0400R	TIE	TIE BLACK L=70MM	1	PCS
⑤	C.045P01.0100R	MOLDING	PVC 45P BLACK	5.5	G
④	C.000000.0000R	MOLDING	PE	2.5	G
③	J.000008.0500R	TIN WIRE	TIN WIRE OD:0.8MM	3.5	G
②	B.01004M.0N05R	CONNECTOR	TTL-PCB(5V) USB A/M CONNECTOR PLASTIC: WHITE	1	PCS
①	A.009X01.0603R	CABLE	UL2464 26AWG(7/0.16TC)*6C(RED,ORANGE,GREEN, BLACK,YELLOW,BROWN)+AL FOIL PVC JACKET COLOR:BLACK OD=5.0±0.1mm L=1780MM	1	PCS
NO.	PART NO	ITEM	DESCRIPTION	Q' TY	UNIT

DELICK®
we move the world

Title: Converter USB 2.0 male > TTL 6 open wires
1.8 m (5 V)

Date	2018 / 02 / 01	Item no.	83116
Unit	mm	Barcode	4043619831166
Projection		File No.	88203
Rev	A		