

NOTES:
1.ELECTRICALTEST:100%OPEN,SHORT&MIS WIRE TEST.
2.CONTACT RESISTANCE:10 ohm,
3.INSULATOR RESISTANCE:5M ohm.
4.HIGH VOLTAGE:DC 300V 0.01sec.
5.MUST BE ROHS COMPLIANT.

NO.	PART NO	ITEM	DESCRIPTION	Q'TY	UNIT
⑥	J0007	TIN WIRE	OD:0.8MM		G
⑤	C0002	MOLDING	PVC 45P BLACK		G
④	C0001	MOLDING	PE		G
③	B0114	CONNECTOR	RJ50 10P10C M	1	PCS
②	B0041	CONNECTOR	USB 2.0 A/M PIN GOLDED SHELL NICKEL PLATED PLASTIC:WHITE	1	PCS
①	A0371	CABLE	NO-UL 26AWG(7/0.16TC)*5C(RED,WHITE,GREEN,BLACK,YELLOW) ID:0.9 OD:3.5MM JACKET:BLACK PVC L=2000MM	1	PCS

Date	2023 / 07 / 04
Unit	mm
Projection	
Rev	A

DELOCK® we move the world

Title: UPS Communication Cable
USB 2.0 Type-A to USB RJ50 2 m

Item no.	67016
Barcode	4043619670161
File No.	88203