

接线表



NOTES:
1.ELECTRICALTEST:100%OPEN,SHORT&MIS WIRE TEST.
2.CONDUCTOR RESISTANCE:2 ohm,
3.INSULATOR RESISTANCE:5M ohm.
4.HIGH VOLTAGE:DC 300V 0.01sec.
5.MUST BE ROHS COMPLIANT.

		LABEL			
⑨		TIE	TIE BLACK L=100MM	1	PCS
⑧		MOLDING	PVC 45P BLACK	13.6	G
⑦		MOLDING	PE	5.5	G
⑥		TIN WIRE	TIN WIRE OD:0.8MM	6.5	G
⑤		SCREW	4-40# SCREW COLOR BLACK	4	PCS
④		CONNECTOR	DC5.5*2.1 FEMALE SHELL NICKEL PLASTIC BLACK	1	PCS
③		CONNECTOR	DB9P/F PIN GOLDED SHELL NICKEL PLASTIC BLACK	2	PCS
②		CABLE	UL1007 26AWG electronic wire, color:Red and Black L=35mm	4	PCS
①		CABLE	UL2464 26AWG(7/0.16TC)*8C+D+AL PVC JACKET COLOR BLACK OD=4.5±0.1mm	1	PCS
NO.	PART NO	ITEM	DESCRIPTION	Q'TY	UNIT

Date	2023 / 10 / 20
Unit	mm
Projection	
Rev	A

DELOCK
we move the world

Title: Serial Cable RS-232 D-Sub 9 female to D-Sub 9 female Power at Pin 9 0.5 m

Item no.	87835
Barcode	4043619878352
File No.	88203