

Delock Wall Socket with 2 x USB Type-A Charging Port 2.8 A

Description

This power socket with a side grounding contact by Delock is for installation in a standard flush-mounted or cavity installation box. In addition to a CEE 7/3 socket with childproof lock, this power socket side grounding contact offers two USB Type-A charging ports. Thus, smartphones, tablets and similar devices can be charged while the socket is still available.



The socket is compatible to switch series with 55 x 55 mm frame window sizes. This includes the switch series of well-known manufacturers such as Gira, JUNG, Busch-Jaeger or Merten.



Item no. 11473

EAN: 4043619114733 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - 1 x power socket CEE 7/3 with childproof lock
 - 2 x USB Type-A charging port max. 2.8 A
 - 3 x screw terminal for PE, N, L
- Rated current: 16 A / 250 V~
- Rated power: 4000 W
- USB Charger:

Input: AC 250 V / 50 Hz / 0.2 A

USB output: max. 5.0 V / 2.8 A total

USB output power: max. 14.0 W total

Average active efficiency 82.91 %

Efficiency at low load (10 %) 78.09 %

No-load power consumption 0.095 W

Short circuit protection

- Suitable for switch series with 55 x 55 mm frame window size
- Mounting depth: 40 mm
- Suitable for standard installation box
- Claw and screw fixing
- Fire retardant plastic housing (UL 94 V-0)





- Dimensions (LxWxH): ca. 80 x 80 x 52 mm
- · Colour: white

System requirements

- Mains supply with grounding
- A free standard installation box

Package content

- Power socket
- User manual

Images











General

Mounting type:	in-wall
Protection:	Input overvoltage protection Short circuit protection

Interface

Connector 1:	1 x 3 pin terminal block screw terminal
Connector 2:	1 x Steckdose CEE 7/3 mit Kindersicherung
connector 3:	2 x USB Type-A female

Physical characteristics

Length:	80 mm
Width:	80.0 mm
Height:	56 mm
Colour:	white