

# Delock Wall Socket with two USB Charging Ports 3.4 A, 1 x USB Type-A and 1 x USB Type-C™

## Description

This power socket with a side grounding contact by Delock is for installation in a standard flush-mounted or cavity installation box. In addition to a CEE 7/3 socket with childproof lock, this power socket side grounding contact offers two USB charging ports. With the two charging ports USB Type-A and USB Type-C™, this socket is also prepared for the future. Thus, smartphones, tablets and similar devices can be charged while the socket is still available.



**Item no. 11489**

EAN: 4043619114894

Country of origin: China

Package: Retail Box

## Suitable for many switch series

The socket is compatible to switch series with 55 x 55 mm frame window sizes. This includes the switch series of well-known manufacturers such as Gira, JUNG, Busch-Jaeger or Merten.

## Specification

- Connectors:
  - 1 x power socket CEE 7/3 with childproof lock
  - 1 x USB Type-A charging port
  - 1 x USB Type-C™ charging port
  - 3 x screw terminal for PE, N, L
- Rated current: 16.0 A / 250 V~
- Rated power: 4000.0 W
- USB Charger:
  - Input: AC 250 V / 50 Hz / 0.2 A
  - USB output: max. 5.0 V / 3.4 A total
  - Output power: max. 17.0 W total
  - Average active efficiency 82.91 %
  - Efficiency at low load (10 %) 78.09 %
  - No-load power consumption 0.095 W
  - Short circuit protection
- Suitable for switch series with 55 x 55 mm frame window size
- Mounting depth: 40 mm
- Suitable for standard installation box
- Claw and screw fixing

- Fire retardant plastic housing (UL 94 V-0)
- Dimensions (LxWxH): ca. 80 x 80 x 44 mm
- Colour: white

---

## System requirements

- Mains supply with grounding
- A free standard installation box

---

## Package content

- Power socket
- User manual

---

## Images



### General

Mounting type:	in-wall
Protection:	Input overvoltage protection Short circuit protection

### Interface

Connector 1:	1 x 3 pin terminal block screw terminal
Connector 2:	1 x Steckdose CEE 7/3 mit Kindersicherung
connector 3:	1 x USB Type-A female 1 x USB Type-C™ female

### Physical characteristics

Length:	80 mm
Width:	80.0 mm
Height:	44 mm
Colour:	white

### Power supply

Input:	AC 100 - 240 V / 50 - 60 Hz / 0.2 A
Output:	5,0 V / 3,4 A