

Delock GSM / UMTS antena SMA muški 0,7 - 1,6 dBi ULA100 1 m vanjska višesmjerni s crna fiksna

Opis

Ova Delock antena omogućuje vam uporabu različitih LTE opsega na otvorenim i u zatvorenim prostorima. U potpunosti je usklađena za GSM, UMTS, LTE, NB-IoT, DECT, Z-Wave, ZigBee i LoRa 868 MHz / 915 MHz.



Predmet br. 12544

EAN: 4043619125449

Zemlja podrijetla: Taiwan,
Republic of China

Pakiranje: Retail Box

Tehnički podaci

- Priključak: 1 x SMA muški
- Frekvencijski opseg:
824 - 960 MHz
1710 MHz - 2170 MHz
- GSM, UMTS, LTE, LoRa, NB-IoT, DECT, Z-Wave, ZigBee
- Pojačanje antene:
824 - 960 MHz: 0,7 dBi
1710 - 2170 MHz: 1,6 dBi
- Impedancija: 50 ohma
- VSWR:
824 - 960 MHz: 4,0
1710 - 2170 MHz: 2,5
- Polarizacija: linearna, vertikalna
- Radna temperatura: -40 °C ~ 85 °C
- Materijal kućišta: polikarbonat
- Stupanj zaštite: IP67
- Boja: crno
- Kabel: koaksijalni

- Vrsta kabela: ULA 100
- Boja kabela: crna
- Promjer kabela: oko 2,79 mm
- Slabljenje kabela: 1,4 dB @ 2500 MHz po metru
- Najmanji polumjer savijanja: 14 mm
- Duljina kabela zajedno s priključkom: oko 1 m
- Mjere (DxŠ): oko 77 x 45 mm




Preduvjeti sustava

- Uređaj sa slobodnim SMA utičnicom

Sadržaj pakiranja

- Antena

Slike



General

Protection category:	IP67
Suitable for indoor:	Yes (Da)
Suitable for outdoor:	Yes (Da)

Interface

priključak:	1 x SMA utikač
-------------	----------------

Technical characteristics

Frequency range:	824 MHz - 960 MHz 1710 MHz - 2170 MHz
Antenna gain:	0,7 dBi 1,6 dBi
Impedancijaa:	50 Ω
Polarisation:	linear vertical
VSWR:	2,5 4,0

Physical characteristics

Materijal kućišta:	Polycarbonat
Cable category:	koaksijalni
Cable type:	ULA 100
Cable attenuation:	0.98 dB @ 1500 MHz per meter
Boja kabela:	crne
Cable length incl. connector:	1 m
Diameter:	45 mm
Najmanji polumjer savijanja:	14 mm
Boja:	crne