

Delock LPWAN Antenna SMA plug 1 - 2 dBi RG-178 1 m PCB internal self adhesive

Description

This LPWAN antenna by Delock allows the usage of the NB-IoT bands indoors.

LPWAN (Low Power Wide Area Network) are radio networks that cover **large distances**. They are characterized by a high reception sensitivity and by a low energy consumption.



Item no. 12620

EAN: 4043619126200

Country of origin: Taiwan,

Republic of China

Package: Zip poly bag

Specification

• Connector: 1 x SMA plug

Frequency range:703 MHz - 824 MHz

832 MHz - 960 MHz

• ZigBee, Z-Wave, GSM, LTE, NB-IoT, LoRa, ISM

• Antenna gain: 1 - 2 dBi

• VSWR: 3.5

• Impedance: 50 Ohm

· Mounting type: self adhesive

• Operating temperature: -10 °C ~ 55 °C

· Housing material: PCB

· Colour: black

Cable type: coaxialCable type: RG-178Cable colour: black

Cable Colour Slack

• Cable diameter: ca. 1.8 mm

• Cable attenuation: 2.9 dB @ 2.4 GHz per meter

Smallest bending radius: 7.5 mm



- Dimensions (LxW): ca. 85.0 x 25.0 mm
- Cable length incl. connector: ca. 1 m

System requirements


• Device with one free SMA port


Package content


• Antenna

Images











General

Mounting type:	Self adhesive
Suitable for indoor:	yes

Interface

connector:

Technical characteristics

Frequency range:	703 MHz - 824 MHz 832 MHz - 960 MHz
Antenna gain:	1 - 2 dBi
Impedance:	50 Ω
Operating temperature:	-10 °C ~ 55 °C
VSWR:	3.5

Physical characteristics

Antenna type:	PCB
Housing material:	FR4
Cable category:	coaxial
Cable type:	RG-178
Cable attenuation:	2.9 dB @ 2.4 GHz per meter
Cable colour:	black
Cable length incl. connector:	1 m
Length:	85 mm
Width:	25 mm
Smallest bending radius:	7.5 mm
Colour:	black