



Delock 3.5" External Enclosure SATA HDD > USB 3.1 Gen 2

Description

In the aluminum enclosure by Delock a 3.5" SATA hard drive can be installed. The housing will be connected via the USB Type-A or USB Type-CTM port to a PC or laptop. The package content includes a USB Type-A connection cable and an adapter to connect the enclosure to a USB Type-CTM port.



Item no. 42591

EAN: 4043619425914 Country of origin: China Package: Retail Box

Specification

- Connectors:
 - external:
 - 1 x SuperSpeed USB 10 Gbps (USB 3.1 Gen 2) Type Micro-B female
 - 1 x DC jack
 - internal:
 - 1 x SATA 6 Gb/s 22 pin plug
- · On / Off switch
- Suitable for all 3.5" SATA HDDs up to 6 Gb/s
- Chipset: Asmedia ASM1351
- Data transfer rate up to 6 Gb/s
- LED indicator for power and access
- Dimensions (LxWxH): ca. 206 x 124 x 32 mm
- · Hot Plug, Plug & Play

Power supply specification

Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.6 A



• Output: 12 V / 2 A

• Ground outside, plus inside

• Dimensions:

inside: ø ca. 2.1 mm outside: ø ca. 5.5 mm length: ca. 11 mm

System requirements

- Windows 7/7-64/8.1/8.1-64/10/10-64, Linux ex Kernel 4.6, Mac ex OS 10.10.x, OS 10.12.5
- PC or laptop with a free USB Type-A or USB Type-C™ port

Package content

- 3.5" external enclosure
- Cable Micro USB 3.1 male to USB Type-A male, length ca. 100 cm
- Adapter USB Type-A female to USB-C™ male
- Stand
- Screws
- External power supply
- User manual

Images









General

Function:	Hot Plug Plug & Play
Suitable for data medium:	3.5"
Supported operating system:	Linux Kernel 4.6 or above Mac OS 10.10 or above Windows 10 32-Bit Windows 7 32-Bit Windows 7 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit

Interface

External:	1 x DC jack 5.5 x 2.1 mm 1 x USB 10 Gbps Type Micro-B female
Internal:	1 x SATA 6 Gb/s 22 pin plug

Technical characteristics

Chipset:	Asmedia ASM1351
Data transfer rate:	10 Gbps

Physical characteristics

Length:	206 mm
Width:	32 mm
Height:	124 mm