

Delock USB Type-C™ Adapter to Gigabit LAN with Power Delivery 100 watt

Description

The adapter by Delock expands a PC or laptop by **one network interface via the USB Type-C™** interface. In addition, the adapter can also be operated on a Thunderbolt™ 3 interface.

USB Power Delivery (USB PD 3.0) support up to 100 watt

The adapter has a USB Type-C™ Power Delivery port to connect the power supply of the laptop or tablet to charge it. The adapter can also be used without a power supply.



Item no. 61026

EAN: 4043619610266

Country of origin: China

Package: Retail Box

Specification

- Connectors:
 - 1 x USB 5 Gbps USB Type-C™ male
 - 1 x Gigabit LAN RJ45 jack
 - 1 x USB Type-C™ PD female (power supply)
- Chipset: Realtek RTL8153B, VIA VL102
- SuperSpeed USB - 5 Gbps specification
- Data transfer rate:
 - Ethernet up to 10 Mbps (Half/Full Duplex)
 - Fast Ethernet up to 100 Mbps (Half/Full Duplex)
 - Gigabit Ethernet up to 1000 Mbps (Half/Full Duplex)
- Compatible with:
 - IEEE 802.3: 10BASE-T
 - IEEE 802.3u: 100BASE-TX
 - IEEE 802.3ab: 1000BASE-T
- Supports Auto MDI-X (automatic detection of standard or crossover network cable)
- Supports Wake On LAN (WOL)
- Supports IEEE 802.3az (Energy Efficient Ethernet)
- Supports IEEE 802.1Q Virtual LAN (VLAN)
- Support full duplex operation with IEEE 802.3x flow control and half duplex operation with back-pressure flow

control

- Supports 9k Jumbo Frames
- Output power for host: max. 100 W
- LED indicator for power and activity
- USB bus powered
- Colour: black
- Cable length incl. connectors: ca. 17 cm

System requirements

- Android 10.0 or above
- Chrome OS
- Linux Kernel 5.11 or above
- Mac OS 11.5.2 or above
- Windows 8.1/8.1-64/10/10-64/11
- iPad Air (4th Generation) or above
- iPad Pro (3rd Generation) or above
- Surface Pro 7
- Device with a free USB Type-C™ port or with a free Thunderbolt™ 3 port

Package content

- USB Type-C™ Gigabit LAN adapter
- User manual

Images



General

| | |
|-----------------------------|--|
| Supported operating system: | Chrome OS Windows 10 32-Bit Windows 10 64-Bit Windows 8.1 32-Bit Windows 8.1 64-Bit Android 10.0 or above iPad Pro (3rd Generation) or above iPad Air (4th Generation) or above Windows 11 Linux Kernel 5.11 or above Mac OS 11.5.2 or above |
| LED indicator: | 2 x |

Interface

| | |
|--------------|---------------------------------------|
| Connector 1: | 1 x USB 5 Gbps USB Type-C™ male |
| Connector 2: | 1 x Gigabit LAN RJ45 jack |
| connector 3: | 1 x USB Type-C™ Power Delivery female |

Technical characteristics

| | |
|---------------------|---|
| Chipset: | Realtek RTL8153B VIA VL102 |
| Data transfer rate: | Gigabit Ethernet up to 100 Gbps Gigabit Ethernet up to 10 Gbps Gigabit Ethernet up to 1000 Mbps |

Physical characteristics

| | |
|---------|-------|
| Colour: | black |
|---------|-------|