

Delock Adaptor USB 2.0 Tip-A > 1 x interfață serială DB9 RS-232 + Adaptor DB25

Descriere scurta

Acest adaptor de la Delock permite conectarea unui dispozitiv cu interfață serială prin intermediul unui port USB Tip-A.



1,8 m

Nr. 61308

EAN: 4043619613083

Țara de origine: China

Pachet: Retail Box

Specification

- Conectori:
 - Cablu:
 - 1 x USB 2.0 Tip-A, tată >
 - 1 x RS-232 seriale DB9, tată
 - Adaptor:
 - 1 x RS-232 seriale DB9, mamă >
 - 1 x RS-232 seriale DB25, tată
- Chipset: FTDI
- Conector serial cu șurub
- Rată transfer date: peste 1 Mbps
- Lungime cablu: aprox. 1,8 m


Cerinte de sistem

- Windows Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64
- PC sau laptop cu un port USB liber

Pachetul contine

- USB 2.0 la 1 x seriale adaptoare
- Adaptor DB9 la DB25
- CD cu drivere
- Manual de utilizare

Imagini



General

| | |
|-----------------------------|---|
| Function: | Plug & Play |
| Specification: | RS-232 (EIA / TIA) USB 1.1 USB 2.0 |
| Supported operating system: | Linux Kernel 2.6 sau superior Mac OS 10.9 sau superior Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows Server 2008 R2 Windows Server 2012 R2 Windows Server 2012 Windows Server 2016 |

Interface

| | |
|-------------|----------------------------|
| Conector 1: | 1 x USB 2.0 Type-A male |
| Conector 2: | 1 x Serial RS-232 DB9 male |

Technical characteristics

| | |
|----------------------|--|
| Chipset: | FTDI FT232RL |
| Data transfer rate: | up to 921.6 Kbps |
| FIFO: | 128 byte 256 Byte |
| Signal transmission: | TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND |
| Data transmission: | asynchronous full duplex |
| Current consumption: | 20 mA |
| UART: | USB to serial UART |

Physical characteristics

| | |
|-------------------------------|-------------|
| Cable colour: | transparent |
| Cable length incl. connector: | 1,8 m |
| Pin finishing: | gold-plated |
| Tipul șurubului: | #4-40 UNC |
| Shielding: | double |
| Colour: | negru |