

Delock Adaptor USB 2.0 Tip-A > 1 x interfață serială DB9 RS-232

Descriere scurta

Acest adaptor de la Delock permite conectarea unui dispozitiv cu interfață serială prin intermediul unui port USB Tip-A.



1,1 m

Specification

- Conectori:
1 x USB 2.0 Tip-A, tată >
1 x RS-232 seriale DB9, tată, cu piulițe
- Chipset: FTDI
- Rată de transfer a datelor de până la 1 Mb/s
- Lungime cablu: cca 1 m

Cerinte de sistem

- Windows Server-2003/Server-2008/Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64
- PC sau laptop cu un port USB Tip-A liber

Pachetul contine

- USB 2.0 la 1 x seriale adaptoare
- CD cu drivere
- Manual de utilizare

Nr. 61364


EAN: 4043619613649

Țara de origine: Taiwan, Republic of China

Pachet: • Retail Box



Imagini



General	
Function:	Plug & Play
Specification:	RS-232 (EIA / TIA) USB 1.1 USB 2.0
Supported operating system:	Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows 10 32-bit Windows 10 64-bit Linux Kernel 2.6 sau superior
Indicator cu LED:	3 x PWR / RXD / TXD
Interface	
Conector 1:	1 x USB 2.0 Type-A male
Conector 2:	1 x Serial RS-232 DB9 male
Technical characteristics	
Chipset:	FTDI 232BL
Data transfer rate:	up to 921.6 Kbps
FIFO:	384 Byte RX 128 Byte TX
Temperatură în stare de funcționare:	0 °C ~ 60 °C
Signal transmission:	TxD, RxD, RTS, CTS, DTR, DSR, DCD, RI, GND
Data transmission:	asynchronous full duplex
Current consumption:	max. 40 mA
Physical characteristics	
Carcasa uitoare:	transparentă
Cable colour:	transparent
Cable length incl. connector:	1,1 m
Tipul șurubului:	#4-40 UNC
Shielding:	double
Colour:	negru