

Delock Adattatore USB 2.0 > 1 x seriale RS-422/485

Descrizione

Questo adattatore Delock consente il collegamento di un dispositivo seriale tramite porta USB Tipo-A.



Articolo n. 62406

EAN: 4043619624065

Paese di origine: China

Pacchetto: Retail Box

Specifiche

- Connettori:
Adattatore:
1 x USB 2.0 Tipo-A maschio >
1 x seriale RS-422/485 D-Sub a 9 pin maschio
Morsettiera:
1 x seriale RS-422/485 D-Sub a 9 pin femmina >
1 x morsettiera a 6 pin
- Chipset: FTDI
- Connettore seriale con dadi
- Velocità di trasferimento dati fino a 230,4 Kbps
- Lunghezza cavo con connettori: ca. 0,8 m

Requisiti di sistema

- Windows Vista/Vista-64/7/7-64/8.1/8.1-64/10/10-64/11
- PC o laptop con porta USB Tipo-A libera

Contenuto della confezione

- USB 2.0 per 1 x seriale RS-422/485 adattatore
- Adattatore per morsetti
- CD contenente il driver
- Manuale utente

Immagini



62406	D09 Buchse/Male		TerminalBlock/Terminal Block
	RS-422	RS-485	RS-422/RS-485
1	Transmit (A-)	T/R (A-)	T/R (A-)
2	Transmit (B+)	T/R (B+)	T/R (B+)
3	Receive (A-)	NC	Receive (A-)
4	Receive (B+)	NC	Receive (B+)
5	Signal GND (SG)	Signal GND (SG)	Signal GND (SG)
6	NC	NC	NC
7	NC	NC	NC
8	NC	NC	NC
9	NC	NC	NC

General

Function:	Plug & Play
Specification:	RS-422 / RS-485 (EIA / TIA) USB 2.0
Supported operating system:	Linux Kernel 2.6 o superiore Mac OS 10.14.1 o superiore Windows 10 32-bit Windows 10 64-bit Windows 7 32-bit Windows 7 64-bit Windows 8.1 32-bit Windows 8.1 64-bit Windows Server 2012 R2 Windows Server 2012 Windows Server 2016 Windows 11
Protection:	ESD (Electrostatic Discharge)

Interface

Connettore 1:	1 x USB 2.0 Type-A male
Connettore 2:	1 x Serial RS-422/485 DB9 male
connector 3:	1 x 6 Pin Terminal Block

Technical characteristics

Chipset:	FTDI 232R
Data transfer rate:	bis zu 230,4 Kbps
Data transmission:	asynchronous Half duplex full duplex differential
UART:	USB to serial UART
Resistor:	Termination resistors 120 Ω
Support:	Modbus

Physical characteristics

Custodia colore:	nero
Materiale custodia:	Plastica
Cable colour:	brown transparent
Cable length incl. connector:	0,8 m
Pin finishing:	gold-plated
Tipo di vite:	#4-40 UNC
Shielding:	doppio