

Delock Audio Converter Digital > Analogue

Description

The audio converter by Delock converts a digital audio signal into an analogue stereo signal. For example a DVD or Blu-ray player can be connected to the input of the device and the signal can be supplied via optical TOSLINK or via S/PDIF coaxial connection. At the output port, the audio signal is transmitted via the RCA connection.



Item no. 62444

EAN: 4043619624447

Country of origin: China

Package: White Box

Technical details

- Connectors:
 - Input:
 - 1 x TOSLINK female S/PDIF
 - 1 x Coaxial female S/PDIF
 - 1 x DC jack
 - Output:
 - 2 x RCA female
- Supported sample rates: 32 / 44.1 / 48 / 96 kHz
- Robust metal housing
- Dimensions (LxWxH): ca. 63 x 41 x 21 mm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm

outside: \varnothing ca. 5.5 mm
length: ca. 9 mm


System requirements

- Digital audio signal
- Connection cable

Package content

- Converter digital > analogue
- Power supply
- User manual

Images



Interface

| | |
|---------|---|
| Output: | 2 x RCA female (red, white) |
| Input: | 1 x Coaxial female S/PDIF 1 x TOSLINK female S/PDIF 1 x 5 V DC female 5,5 mm x 2,1 mm |

Physical characteristics

| | |
|-------------------|---------|
| Housing colour: | black |
| Housing material: | Plastic |
| Length: | 63 mm |
| Width: | 41 mm |
| Height: | 21 mm |