

# Delock HDMI Audio Extractor

## Description

This adapter by Delock can be used to extract the audio signal from an HDMI transmission. While the video signal is displayed on a TV or monitor, the audio signal can be sent digital (S/PDIF) or analogue (stereo) to other devices, such as headphones or a surround receiver.



## Specification

- Connectors:
  - Input:
    - 1 x HDMI-A 19 pin female
    - 1 x DC 5.5 x 2.1 mm female
  - Output:
    - 1 x HDMI-A 19 pin female
    - 1 x 3.5 mm 3 pin stereo jack female (audio)
    - 1 x TOSLINK female S/PDIF
    - 1 x RCA female S/PDIF
- Switchable between stereo and 5.1 channel
- High Speed HDMI, 3D and HDCP 1.4
- Output with HDMI repeater function
- Resolution up to Full-HD 1080p
- Video bandwidth up to 225 MHz / 2.25 Gbps per channel, max. 6.75 Gbps
- Supports all common 2.0 and 5.1 audio formats: LPCM, Dolby Digital, DTS Audio
- Supported sample rates: 16 / 20 / 24 bit, 32 / 44.1 / 48 / 88.2 / 96 kHz (depending on the system and the connected devices)
- CEC and HDMI audio routed to the output (pass-through)
- Robust metal housing
- Power consumption: max. 2.5 W
- Dimensions (LxWxH): ca. 70 x 60 x 20 mm

## Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
  - inside:  $\varnothing$  ca. 2.1 mm
  - outside:  $\varnothing$  ca. 5.5 mm
  - length: ca. 9 mm

## Package content

- HDMI Audio Extractor
- Mounting brackets and screws
- Power supply

## Item no. 62492

EAN: 4043619624928

Country of origin: China

Package: Retail Box



Images

